

SPECIFICATION SHEET



DIMENSION(mm)

| HEM COLOR | | | | |
|-----------|-------|------|--------|-------|
| S | M | L | XL | XXL |
| White | Green | Grey | Yellow | Black |
| 230 | 240 | 250 | 260 | 270 |

Tolerance ±5.0mm

EN388:2016 / ISO 13997

| | | | | | | |
|--------------------|---|---|---|---|---|---|
| ABRASION | 0 | 1 | 2 | 3 | 4 | |
| CIRCULAR BLADE CUT | 0 | 1 | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | |
| LINEAR BLADE CUT | A | B | C | D | E | F |

MELANGE GLASS FIBER LINER

BLACK NITRILE FOAM PALM COATED GLOVES

Glass Fiber Blended HPPE and Polyester

- + Seamless Stretchable Liner with Dexterity
- + Comfortable fit with High Strength
- + High Protection from Cuttable Hazard

Oily Away Nitrile Foam Palm Finished

- + Provide Secure Grip in Oil Applications
- + Light with Unique Breathable and Soft Tactility

APPLICATIONS

- + Oily Working / Heavy Industrial Applicants
- + Ideal for Handling Sharp Metal, Glass, and Ceramic
- + Automobile Industries / Mechanical Assembly
- + Construction / Wiring Operation / Manufacturing

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used.

About 5-10 minute cycle time should be employed.
Tumble dry on low - maximum temperature 140°F(60°C).

TECHNICAL DATA

| | |
|----------|------------------------------------|
| MATERIAL | Glass Fiber/HPPE/Polyester/Spandex |
| KNITTING | 13 Gauge |
| COATING | Nitrile Foam Palm Finished |
| SIZE | S / M / L / XL / XXL |
| ORIGIN | South Korea |