



DIMENSION(mm)

HEM COLOR				
S	M	L	XL	XXL
White	Green	Grey	Yellow	Black
230	240	250	260	270

Tolerance ±5.0mm

EN388:2016 / ISO 13997

ABRASION	0	1	2	3	4	
CIRCULAR BLADE CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	
PUNCTURE	0	1	2	3	4	
LINEAR BLADE CUT	A	B	C	D	E	F

MELANGE SPAN-NYLON LINER

NBR FOAM PALM COATED GLOVES

Spandex blended Nylon

- + Seamless High Stretchable Liner with Optimal Dexterity
- + Extremely Comfortable fit with High Ventilation
- + Less Hand Fatigue with High Breathable

Oily Away NBR Foam Palm Finished

- + Provide Secure Grip in Oil Applications
- + Light with High Breathable and Soft Tactility

APPLICATIONS

- + Oily Working
- + Mechanical Assembly / General Maintenance
- + Using Tools and Instrument
- + Construction / Manufacturing

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used.

About 5-10 minute cycle time should be employed.
Tumble dry on low - maximum temperature 140°F(60°C).

TECHNICAL DATA

MATERIAL	Spandex blended Nylon Fiber
KNITTING	15 Gauge
COATING	NBR Foam Palm Finished
SIZE	S / M / L / XL / XXL
ORIGIN	South Korea