



### DIMENSION(mm)

| HEM COLOR |       |      |        |       |
|-----------|-------|------|--------|-------|
| S         | M     | L    | XL     | XXL   |
| White     | Green | Grey | Yellow | Black |
| 230       | 240   | 250  | 260    | 270   |

Tolerance ±5.0mm

### EN388:2016 / ISO 13997

| ABRASION           | 0 | 1 | 2 | 3 | 4 |   |
|--------------------|---|---|---|---|---|---|
| CIRCULAR BLADE CUT | 0 | 1 | 2 | 3 | 4 | 5 |
| TEAR               | 0 | 1 | 2 | 3 | 4 |   |
| PUNCTURE           | 0 | 1 | 2 | 3 | 4 |   |
| LINEAR BLADE CUT   | A | B | C | D | E | F |

### WHITE POLYESTER LINER

### WHITE PU PALM COATED GLOVES

#### Soft 300 Denier Polyester

- + Soft Fabric knitted with 100% Polyester Filament Yarns
- + Comfortable fit with High Ventilation and Sensitivity
- + Less Hand Fatigue with High Breathable

#### Soft PU Palm Finished

- + Provide Secure Grip in Dry and Wet Environments
- + High Protection from Abrasion
- + Durable, Washable and Reusable

### APPLICATIONS

- + Assembling Process of Light Electronics
- + Precision Work
- + Lab Work
- + Inspection of Medicine

### CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used.

About 5-10 minute cycle time should be employed.

Tumble dry on low - maximum temperature 140°F(60°C).

### TECHNICAL DATA

| MATERIAL | 150 Denier Polyester X 2 Threads |
|----------|----------------------------------|
| KNITTING | 13 Gauge                         |
| COATING  | PU PALM Finished                 |
| SIZE     | S / M / L / XL / XXL             |
| ORIGIN   | South Korea                      |