5232Z

SPECIFICATION SHEET

MELANGE GLASS FIBER LINER PU PALM COATED GLOVES

Glass Fiber Blended HPPE and Polyeter

+ Seamless Stretchable Liner with Dexterity
+ Comfortable fit with High Strength
+ High Protection from Cuttable Hazard

Soft PU Palm Finished

+ Provide Secure Grip in Dry and Wet Environments
+ High Protection from Abrasion

APPLICATIONS

+ Ideal for Handling Sharp Metal, Glass, and Ceramic
+ Automobile Industries / Mechanical Assembly
+ Construction / Manufacturing
+ Industrial Applicants / Wiring Operations

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used.

About 5-10 minute cycle time should be employed.
Tumble dry on low - maximum temperature 140°F(60°C).

EN 388

DIMENSION(mm)

HEM COLOR				
S	M	L	XL	XXL
White	Green	Grey	Yellow	Black
230	240	250	260	270

Tolerance ±5.0mm

EN388:2016 / ISO 13997

ABRASION	0	1	2	3	**4**	
CIRCULAR BLADE CUT	0	1	2	3	4	5
TEAR	0	1	2	3	**4**	
PUNCTURE	0	1	**2**	3	4	
LINEAR BLADE CUT	A	B	C	**D**	E	F

TECHNICAL DATA

MATERIAL	Glass Fiber/HPPE/Polyester/Spandex
KNITTING	13 Gauge
COATING	PU Palm Finished
SIZE	S / M / L / XL / XXL
ORIGIN	South Korea

DUKWONGLOVE 덕원글러브

DUKWON GLOVE CO.
#7, Gongdan 1-gil, Gimcheon-si, Gyeongbuk (39541), KOREA
TEL: +82-54-437-1789 / FAX: +82-54-437-1795
E-mail: hb.heo@dwglove.kr / www.dwglove.kr